



Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

About IDT

Products

Applications

Support

myIDT

Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > Clock Synthesizer by Chipset Vendor > Desktop Chipsets > 954148 > 954148AGLF

Add to myIDT [?]

954148AGLF

Category: **Desktop Chipsets**

954148 Generic Part: Market Group: PC CLOCK Description: PC MAIN CLOCK

General Description ICS954148 follows the Intel CK410-compliant clock specification. This clock synthesizer provides

a single chip solution for next generation P4 Intel processors and Intel chipsets. ICS954148 is driven with a

14.318MHz

Output Features:

• 2 - 0.7V current-mode differential CPU pairs • 1 - 0.7V current mode differential SATA pair

• 1 - 0.7V current mode differential DOT 96/100MHz pair

• 6 - PCI (33MHz)

• 1 - USB, 48MHz

• 2 - REF, 14.318MHz

• 7 - PCI-Express 0.7V current differential pairs

You may also like..



Parameters

| Package | TSSOP 56 (PAG56) |
|-------------------------|------------------|
| Voltage | 3.3 V |
| Package | TSSOP 56 |
| Speed | NA |
| Temperature | С |
| Status | Active |
| Sam ple | Yes |
| Minimum Order Quantity | 102 |
| Factory Order Increment | 34 |

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

| Туре | Title | Size | Revision Date | |
|------|------------------------|-------|---------------|--|
| Misc | PC Clocks Contact Info | 61 KB | 05/29/2007 | |

Package

| Description | TSSOP 6.10 MM | |
|----------------------------------|-----------------------------|--|
| Class | PLASTIC | |
| Moisture Sensitivity Level (MSL) | 1 | |
| Category | Green | |
| Moisture Exposure Floor Life | Unlimited @ <30°C/85% RH | |
| Peak Reflow Temprature | 260°C | |
| Rebake Conditions | N/A | |
| Length | 14.0 | |
| Mark | G | |
| Width | 6.1 | |
| Pitch | 0.5 | |
| Thickness | 1.0 | |
| Status | Active | |